



Long Distance, High Bandwidth

KW8400 KW8500 Series **P2P MIMO** WiTDM® Outdoor Bridge 250Mbps @15Km / 220Mbps @20Km / 160Mbps @35Km / 110Mbps @50Km 4.8~6.2 GHz

Formosa Wireless Broadband product line are adopting Wireless TDMA concept to provide an affordable and reliable rural connectivity. All of products are high-performance outdoor-deployable wireless bridge that provides wireless connectivity between multiple network locations. With the high throughput and long-distance transmission, it is the appropriate backhaul solution for Carriers, Service Providers and Enterprises.

Key Features & Benefits



- Anti-Interference
- IP67/68 Qualified / Reliable Outdoor Enclosure
- Waterproof
- Vent design
- TDD QoS
- Good Balance on low Cost and High Performance
- Actual reachable testing range > 50 km
- High throughput
- Support point to point, CPE for point to multi point
- Network Topology MAP
- Software Features
- High security (AES128)
- Ease of Installation (Real time Link Test for Local and Remote RSSI)
- Transmit Power Control
- Bandwidth Control
(5MHz, 10MHz, 15MHz, 20MHz, 30MHz, 40MHz, 52MHz)
- Wireless TDMA (TDD Mode)
- On-Board GPS Support (Option)
- Extra Channel Bandwidth Selection – 6 / 7 / 8 / 12 / 14 MHz (Option)
- **KW8400 Series (Single Radio), KW8500 Series (Dual Radios)**

WiTDM®

TOUCH AND CONNECT!™



WNet
Green Network™



TOUCH AND CONNECT!™



WiNet
Green Network™

WiVIEW 2, Managed Tool

No	Status	Model Name	IP Address	Location	Routing	Description
1	●	KWA-O1850-I	192.168.3.1		192.168.3.2	WIFDD
2	●	KWA-O1850-I	192.168.3.2		192.168.3.1	WIFDD
3	●	KWA-O1850-I	192.168.3.3		192.168.3.4	WIFDD
4	●	KWA-O1850-I	192.168.3.4		192.168.3.3	WIFDD
5	●	KWA-O8800-I	192.168.3.5		192.168.3.6	WITDM
6	●	KWA-O8800-I	192.168.3.6		192.168.3.5	WITDM
7	●	KWG-O6020-I	192.168.3.7		192.168.3.10	BGN_AP
8	●	KWA-O6020-I	192.168.3.8		192.168.3.9	Bridge
9	●	KWA-O6020-I	192.168.3.9		192.168.3.8	Bridge
10	●	KWA-O670R	192.168.3.10		192.168.3.7	BGN_Repeater



Bridge Location on the MAP

HARDWARE	
LAN	1 x 10/100/1000 BaseT RJ-45 with Auto-MDIX
Power Over Ethernet (PoE)	Yes (802.3at)
Default Button	Yes
Enclosure	Metal Case, IP68
Surge Protect	Surge Voltage 6KV / Discharge Current 5KA / Response Time < 5ns Standard: IEC64000-4-5
Power Consumption	5W (1RF) / 7W (2RF)
FEATURE	
Operating Mode	Bridge (PTP) / P2MP CPE
Link Test Tool	Yes (Real Time Local and Remote RSSI)
Radio Bandwidth	5MHz, 10MHz, 15MHz, 20MHz, 30MHz, 40MHz, 52MHz
TDMA	Yes
TDM Coordination	Yes
QoS	TDD / 802.1P
Channel Selection	Yes
Auto Channel	Yes
DFS/TPC	Yes
Spanning Tree (STP)	Yes
VLAN	Yes (802.1Q)
GPS Coordinates	Yes
GPS	Yes (Option)
Space In Meters	Yes (Auto)
NTP Client	Yes
CLI	Yes (SSH)
Backup / Restore	Yes
System Log	Yes
Hot Standby Backup	Yes (KW50-08500)
Dual Firmware Image	Yes (Redundant)
Performance	150,000 pps
Remote Log Server	Yes
SECURITY	
Encryption	AES 128bit
MANAGEMENT	
Web Base Management	Yes
SNMP	V2, V3 Private MIB, 802.11 MIB
Windows Tool	Yes, WiVIEW 2
Information	Device name, IP address, MAC address, Frequency, RSSI
PHYSICAL	
Operating Temperature	-30 ~ 80C
Operating Humidity	10 ~ 95% RH

Model	Antenna dBi	Output Power dBm	Sensitivity dBm	Dimension mm	Weight Kg
KW50-O8400	2x N Jack	25	-95	259 x 250 x 75	1.8
KW50-O8400-I	2x2 20 dBi	25	-95	380 x 380 x 90	3.0
KW50-O8500	4x N Jack	25 / 25	-95 / -95	259 x 250 x 75	1.9

Modulation	BPSK		QPSK		16QAM		64QAM		
	FEC								
	1/2	1/2	3/4	1/2	3/4	2/3	3/4	5/6	
Throughput @5MHz Mbps	1	2	3	10	15	20	23	25	
Throughput @10MHz Mbps	2	5	7	21	31	43	48	53	
Throughput @15MHz Mbps	3	7	11	30	45	59	65	70	
Throughput @20MHz Mbps	5	10	15	48	72	95	105	112	
Throughput @30MHz Mbps	7	16	24	74	108	137	145	164	
Throughput @40MHz Mbps	10	21	33	99	144	182	193	220	
Throughput @52MHz Mbps	11	23	37	112	163	205	218	249	
Sensitivity @ 20MHz dBm	-90	-89	-87	-84	-81	-78	-76	-74	
Output Power @ 20MHz dBm	26	25	25	24	24	23	23	23	

Customized Frequency

300MHz / 400MHz / 700MHz / 900MHz / 1.8~1.9GHz / 2.2~2.3GHz / 2.3~2.5GHz / 3.3~3.4GHz / 4.4~6.1GHz /





TOUCH AND CONNECT!™

WiTDM®

 WiNet
 Green Network™

Spec of Build-in Antenna – KW50-O8400-I

Radiation Patterns



KW50-O8400-I



KW50-O8400
KW50-O8500



WiTDM®

TOUCH AND CONNECT!™

WNet
Green Network™